

MM332 INSTALLATION INSTRUCTIONS


3rd Gen Poly Motor Mounts

Tools required:

- Basic Hand Tools and Socket Set
- Jack and Jack Stands

Instructions:

- 1) REMOVE THE NEGATIVE BATTERY TERMINAL LEAD TO CUT POWER FOR THE ENTIRE VEHICLE.
- **2)** Raise the vehicle and support on jack stands on the frame.
- 3) Depending on how much access you have to remove the nuts on the back side of the motor mounts, you may have to remove the coil springs as shown in IMAGE 1.
- 4) Using a jack and block of wood, support the motor on the balancer and take weight off the motor mounts.
- 5) Using a 5/8" and 11/16" wrench and socket, loosen the thru bolt connecting the motor mount to the motor stand.
- 6) Using a 13mm socket and wrench, remove the three (3) screws holding the motor stand to the block and remove the three (3) nuts and bolts holding the mounts the k-member on each side.



NOTE: Both the motor mount and the motor stands need to be removed together at the same time.

- 7) The passenger and driver motor stand look very similar, but are different, please take note of which mount is which. SEE IMAGE 3 and 4.
- 8) Outside of the vehicle, remove the thru-bolt and install your new motor mount with a thru-bolt the same way it was removed.
- 9) Re-install the motor mounts and fasten all bolts. Torque to the specs listed below.

WWW.BMRSUSPENSION.COM





MM332 INSTALLATION INSTRUCTIONS

3rd Gen Poly Motor Mounts

Torque Specs:

- Motor Stand to Block 40ftlbs
- Motor Mount to K-Member 40ftlbs
- Motor Mount to Motor Stand Thru Bolt 55ftlbs





WWW.BMRSUSPENSION.COM

This product is an aftermarket accessory and not designed by the vehicles manufacturer for use on this vehicle. As such, buyer assumes all risk of any damage caused to vehicle/person during installation or use of this product.